

TAKEUCHI
From World First to World Leader

FULL PRODUCT LINE



Excavators - Track Loaders - Skid Steers - Wheel Loaders

COMPACT EXCAVATORS

Takeuchi was the first company to introduce compact excavators to the North American market, setting the stage for one of the fastest growing product segments ever released in the compact construction equipment industry.

Models range in operating weight from nearly 2,400 pounds to just over 34,400 pounds, with dig depths close to 18 feet.

All Takeuchi excavators are rugged, dependable and productive. They provide exceptional value, demonstrate outstanding performance, and are measured by their longevity in the field.



TB210R



TB216



TB230



TB235-2



TB240

Model	Operating Weight	Engine Horsepower	Maximum Digging Depth	Maximum Reach
TB210R	2,370 lb (1,075 kg)	11.7 hp (8.7 kW)	5 ft 9.1 in (1,755 mm)	10 ft 9.4 in (3,285 mm)
TB216*	3,902 lb (1,770 kg)	15.0 hp (11.2 kW)	7 ft 10 in (2,390 mm)	13 ft 5 in (4,090 mm)
TB216H**	4,277 lb (1,940 kg)	14.9 hp (11.1 kW) 14.2 hp (10.6 kW)	7 ft 10 in (2,390 mm)	13 ft 5 in (4,090 mm)
TB230*	6,360 lb (2,885 kg)	24.4 hp (18.2 kW)	9 ft 3.6 in (2,835 mm)	15 ft 10.9 in (4,850 mm)
TB235-2*	7,418 lb (3,365 kg)	24.4 hp (18.2 kW)	10 ft 7.8 in (3,245 mm)	17 ft 2.9 in (5,255 mm)
TB240*	8,570 lb (3,890 kg)	35.8 hp (26.7 kW)	11 ft 4.4 in (3,465 mm)	18 ft 2.3 in (5,545 mm)
TB250-2*	10,957 lb (4,970 kg)	39.0 hp (29.1 kW)	12 ft 4.8 in (3,780 mm)	20 ft 1.0 in (6,120 mm)
TB260*	12,125 lb (5,500 kg)	47.6 hp (35.5 kW)	12 ft 9.4 in (3,895 mm)	20 ft 6.9 in (6,270 mm)
TB290*	18,630 lb (8,450 kg)	69.2 hp (51.6 kW)	15 ft 0 in (4,580 mm)	24 ft 5 in (7,435 mm)
TB2150*	34,480 lb (15,640 kg)	114.0 hp (85.0 kW)	17 ft 10.4 in (5,445 mm)	28 ft 8.9 in (8,760 mm)
TB280FR* Full Rotation	18,810 lb (8,530 kg)	69.2 hp (51.6 kW)	14 ft 11 in (4,540 mm)	23 ft 7.0 in (7,195 mm)

*Takeuchi Fleet Management available on select models. TB216 S/N 216101378 and up. **TB216H Hybrid Standard w/ Diesel Engine and Electric

**2 YEAR
2,000 HOUR
FULL MACHINE
WARRANTY**



TB250-2



TB260



TB290



TB2150



TB280FR

	Maximum Bucket Breakout Force	Traction Force	Auxiliary Hydraulic Flow	Maximum Travel Speed High
	2,518 lb (1,142 kg)	2,878 lb (1,305 kg)	5.9 gal (22.2 L/min)	2.3 mph (3.7 km/hr)
	4,250 lb (1,928 kg)	4,361 lb (1,978 kg)	8.9 gpm (33.6 L/min)	2.6 mph (4.2 km/hr)
	4,250 lb (1,928 kg)	4,361 lb (1,978 kg)	8.9 gpm (33.6 L/min)	2.6 mph (4.2 km/hr)
	6,471 lb (2,935 kg)	6,340 lb (2,876 kg)	13.4 gpm (50.6 L/min)	3.2 mph (5.2 km/hr)
	9,127 lb (4,140 kg)	9,112 lb (4,130 kg)	15.8 gpm (60.0 L/min)	2.7 mph (4.4 km/hr)
	9,959 lb (4,517 kg)	9,533 lb (4,324 kg)	17.1 gpm (64.9 L/min)	3.3 mph (5.3 km/hr)
	10,430 lb (4,731 kg)	12,320 lb (5,588 kg)	24.2 gpm (91.7 L/min)	3.2 mph (5.2 km/hr)
	12,756 lb (5,786 kg)	14,006 lb (6,353 kg)	27.0 gpm (102.2 L/min) *11.6 gpm (43.9 L/min)	3.0 mph (4.9 km/hr)
	16,565 lb (7,514 kg)	19,780 lb (8,972 kg)	26.4 gpm (100.0 L/min) *14.5 gpm (55.0 L/min)	3.1 mph (5.0 km/hr)
	22,190 lb (6,618 kg)	32,600 lb (14,786 kg)	59.0 gpm (224.0 L/min) *14.5 gpm (55.0 L/min)	3.4 mph (5.5 km/hr)
	16,335 lb (7,409 kg)	19,783 lb (8,973 kg)	39.0 gpm (148.0 L/min) *15.0 gpm (58.0 L/min)	3.2 mph (5.2 km/hr)

Electric Motor. See your dealer for details.

*Secondary Auxiliary Flow

**2 YEAR
2,000 HOUR
FULL MACHINE
WARRANTY**



TL6R

Model	Operating Weight	Traction Force	Tipping Load	Rated Operating Capacity
TL6R*	7,480 lb (3,395 kg)	8,655 lb (3,926 kg)	5,269 lb (2,390 kg)	1,841 lb (835 kg)
TL8*	8,455 lb (3,835 kg)	9,127 lb (4,140 kg)	6,020 lb (2,731 kg)	2,105 lb (955 kg) *2,323 lb (1,054 kg)
TL10V2*	9,950 lb (4,515 kg)	9,730 lb (4,410 kg)	7,205 lb (3,268 kg)	2,520 lb (1,140 kg)
TL12R2*	12,300 lb (5,580 kg)	14,010 lb (6,353 kg)	8,629 lb (3,915 kg)	2,975 lb (1,349 kg)
TL12V2*	12,860 lb (5,835 kg)	14,006 lb (6,353 kg)	11,737 lb (5,324 kg)	4,107 lb (1,863 kg)

*Takeuchi Fleet Management available on select models. See your dealer for details.

*w/Optional Counterweight

COMPACT TRACK LOADERS

Meeting the latest EPA Final Tier 4 requirements, Takeuchi compact track loaders continue to evolve and improve allowing them to maintain a competitive edge.

These compact track loaders are powerful and efficient, and each is designed and engineered to provide superior value, durability, power, and maneuverability.

Standard equipment includes precision pilot controls, two speed travel, cushioned boom cylinders, hydraulic self leveling and deluxe high back suspension seat.

The robust frame and undercarriage demonstrates our commitment to quality and functionality providing a platform that will deliver many years of trouble free service in the most extreme conditions.



TL8



TL10V2



TL12R2



TL12V2

Engine Horsepower	Bucket Breakout Force	Lift Arm Breakout Force	Auxiliary Hydraulic Flow	Maximum Travel Speed High
65.2 hp (48.6 kW)	5,930 lb (2,690 kg)	4,860 lb (2,205 kg)	17.8 gpm (67.4 L/min)	6.2 mph (10.0 km/hr)
74.3 hp (55.4 kW)	6,856 lb (3,110 kg)	6,709 lb (3,100 kg)	18.4 gpm (69.5 L/min) *33.0 gpm (124.9 L/min)	6.8 mph (11.0 km/hr)
74.3 hp (55.4 kW)	6,520 lb (2,960 kg)	5,400 lb (2,450 kg)	18.8 gpm (71.2 L/min) *32.8 gpm (124.0 L/min)	7.0 mph (11.3 km/hr)
111.3 hp (83.0 kW)	8,210 lb (3,722 kg)	8,075 lb (3,633 kg)	23.2 gpm (88.0 L/min) *40.4 gpm (153.0 L/min)	7.3 mph (11.8 km/hr)
111.3 hp (83.0 kW)	7,874 lb (3,571 kg)	7,109 lb (3,225 kg)	23.2 gpm (88.0 L/min) *40.4 gpm (153.0 L/min)	7.8 mph (11.8 km/hr)

*w/Optional High flow

SKID STEER LOADERS

The TS80s skid steers provide an outstanding blend of power and performance, durability and operator comfort. The Takeuchi skid steers feature class leading ground clearance and rear departure angles, high travel speeds, excellent tractive effort, and powerful digging forces.

These skid steer loaders are sure to meet your needs, whether it is removing snow, loading trucks, unloading pallets, working construction, or doing road and bridge work, Takeuchi has the radial or vertical lift path skid steer to help complete your toughest tasks.



TS80R2



TS80V2

Model	Operating Weight	Traction Force	Tipping Load	Rated Operating Capacity	Engine Horsepower
TS80R2	7,950 lb (3,606 kg)	8,700 lb (3,946 kg)	*5,650 lb (2,562 kg)	*2,825 lb (1,281 kg)	74 hp (55.0 kW)
TS80V2	8,965 lb (4,066 kg)	8,700 lb (3,946 kg)	*7,000 lb (3,175 kg)	*3,500 lb (1,588 kg)	74 hp (55.0 kW)

*w/Foundry Bucket

*w/Foundry Bucket

**2 YEAR
2,000 HOUR
FULL MACHINE
WARRANTY**



Bucket Breakout Force	Lift Arm Breakout Force	Auxiliary Hydraulic Flow	Maximum Travel Single Speed	Maximum Travel Optional Two-Speed
5,845 lb (2,651 kg)	7,080 lb (3,211 kg)	21.5 gpm (81.0 L/min) *31.0 gpm (117.3 L/min)	8.2 mph (13.1 km/hr)	11.0 mph (17.7 km/hr)
5,920 lb (2,685 kg)	6,200 lb (2,812 kg)	26.0 gpm (98.4 L/min) *31.0 gpm (117.3 L/min)	8.2 mph (13.1 km/hr)	11.0 mph (17.7 km/hr)

*w/Optional High flow

**2 YEAR
2,000 HOUR
FULL MACHINE
WARRANTY**



TW60 Series 2

Model	Operating Weight	Traction Force	Tipping Load Straight	Tipping Load Full Turn	Rated Operating Capacity
TW60 SERIES 2	10,692 lb (4,850 kg)	8,818 lb (4,000 kg)	6,689 lb (3,034 kg)	5,906 lb (2,679 kg)	2,953 lb (1,340 kg)
TW65 SERIES 2	11,354 lb (5,150 kg)	9,217 lb (4,180 kg)	9,171 lb (4,160 kg)	8,100 lb (3,674 kg)	4,050 lb (1,837 kg)
TW80 SERIES 3	12,700 lb (5,760 kg)	12,049 lb (5,466 kg)	9,742 lb (4,419 kg)	8,602 lb (3,902 kg)	4,301 lb (1,951 kg)
TW95	18,188 lb (8,250 kg)	13,592 lb (6,165 kg)	14,307 lb (6,490 kg)	12,652 lb (5,739 kg)	6,326 lb (2,870 kg)

COMPACT WHEEL LOADERS

The compact design of the Takeuchi wheel loaders allows them to maneuver in tight spaces with minimal damage to lawns, pavement, or other sensitive surfaces.

They provide incredible reach and dump height for outstanding material handling, and the spacious operator's station is elevated giving the operator greater visibility.

These wheel loaders deliver power with precise control for increased productivity, and lower operational and maintenance cost.



TW65 Series 2



TW80 Series 3



TW95

	Engine Horsepower	Bucket Breakout Force	Lift Arm Breakout Force	Auxiliary Hydraulic Flow	Maximum Travel Speed High	Machine Width	Machine Height
	61.2 hp (45.6 kW)	6,294 lb (2,855 kg)	6,002 lb (2,722 kg)	15.2 gpm (57.5 Lpm)	12.4 mph (20.0 km/hr) *17.4 mph (28.0 km/hr)	6 ft 3.0 in (1,905 mm)	8 ft 6.4 in (2,599 mm)
	73.0 hp (54.0 kW)	11,600 lb (5,262 kg)	10,319 lb (4,680 kg)	16.4 gpm (62.0 L/min)	12.4 mph (20.0 km/hr) *24.8 mph (40.0 km/hr)	6 ft 1.5 in (1,870 mm)	8 ft 10 in (2,689 mm)
	73.0 hp (54.0 kW)	13,960 lb (6,333 kg)	12,387 lb (5,618 kg)	16.4 gpm (62.0 L/min)	12.4 mph (20.0 km/hr) *24.8 mph (40.0 km/hr)	6 ft 9 in (2,050 mm)	8 ft 11.5 in (2,730 mm)
	114.0 hp (85.0 kW)	15,873 lb (7,200 kg)	18,077 lb (8,200 kg)	26.4 gpm (100.0 Lpm)	12.4 mph (20.0 km/hr) *24.9 mph (40.0 km/hr)	7 ft 1.8 in (2,180 mm)	9 ft 7.4 in (2,932 mm)

*w/Road Gear Option

TOUGH, POWERFUL, RELIABLE







TAKEUCHI

© 2019 Takeuchi Manufacturing [U.S.], Ltd. All Rights Reserved. Printed in the U.S.A. In accordance with our established policy of continued improvement, specifications and features are subject to change without notice. Pictures may show optional equipment.
FORM: Full Product Line Brochure Jan. 2020

US Headquarters
Pendergrass, Georgia
706.693.3600
sales@takeuchi-us.com
www.takeuchi-us.com