



EARTHMAX SR 46 (E-4) for rigid haul trucks is BKT's innovative response to severe rocky, abrasive and harsh mining environments. This tire has been specifically designed to carry heavy loads offering superior resistance to cuts and chips as well as a long tire life-cycle. The All Steel casing and belts provide extraordinary protection against shocks, fatigue and flats to maximize uptime and enhance productivity. EARTHMAX SR 46 (E-4) features a special lug block pattern with circumferential groove to optimize the cornering performance with minimum tread face damage.



Corporate Office

Balkrishna Industries Ltd.

BKT HOUSE, C/15, Trade World, Kamala Mills Compound, Senapati Bapat Marg, Lower Parel, Mumbai - 400013, India
Tel: (+91) 22-6666 3800 - Fax: (+91) 22-6666 3898/99 - e-mail: info@bkt-tires.com - bkt-tires.com

BKT Europe srl

Viale Della Repubblica, 133
20831 Seregno (MB), Italy
Tel: (+39) 0362 33 03 28
(+39) 0362 32 51 07
Fax: (+39) 0362 23 24 72

BKT USA Inc.

202 Montrose West Ave. Suite 240
Copley, Ohio 44321
Tel: (+1) 330 836 1090
Fax: (+1) 330 836 1091
Toll Free: (+1) 888 660 0662

BKT Tires (CANADA) Inc.

55 York Street, Suite 401
Toronto, Ontario M5J 1R7, Canada
Tel: AG/IND (+1) 905 641 5636
OTR (+1) 780 888 5667
Fax: (+1) 416 229 1711



EARTHMAX SR 46 (E-4)
RADIAL OTR TIRES




HARSH AND ROCKY ENVIRONMENTS? EARTHMAX SR 46 (E-4) IS THE SOLUTION!


EARTHMAX SR 46 (E-4) RADIAL OTR TIRES

EARTHMAX SR 46 (E-4) is the innovative response to all hazards and threats coming up every day in these environments. It's the ideal tire for rigid dump trucks since it has been specially designed for heavy load haulage featuring outstanding resistance to cuts, abrasions and punctures.






Safety



Productivity



Operational Efficiency



EARTHMAX SR 46 (E-4) has a particularly strong casing and an All Steel structure to ensure exceptional **protection against any kind of stress, impacts and tears**. This leads to a maximum number of operating hours. All this turns into a **considerably longer tire life-cycle** along with **increased productivity and reduced machine downtime**.

Moreover, the tread design made of a **special block pattern with a circumferential groove** provides excellent stability and exceptional cornering performance, minimizing the risk of tread face damage. Extraordinary self-cleaning qualities and outstanding traction complete the picture of this first-class tire!

Ø 49"	TIRE SIZE	TRA CODE	STAR RATING	LI/SS	TYPE	VERSION	TKPH	O.W. (MM)	O.D. (MM)	SLR (MM)	RC (MM)	TREAD DEPTH (MM)	RIM	
													REC.	ALT.
	27.00 R 49	E4	**	223 B	TL	CRC	455	746	2688	1225	8165	68.0	19.50/4.0	-
	27.00 R 49	E4	**	223 B	TL	HRC	655	746	2688	1225	8165	68.0	19.50/4.0	-
	27.00 R 49	E4	**	223 B	TL	STD	590	746	2688	1225	8165	68.0	19.50/4.0	-

CRC: CUT RESISTANT COMPOUND - HRC: HEAT RESISTANT COMPOUND - STD: STANDARD COMPOUND

Bar	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
km/h	Load capacity (kg/tire)								
50	20600	21800	22400	23000	23600	25000	25750	26500	27250

Ø 51"	TIRE SIZE	TRA CODE	STAR RATING	LI/SS	TYPE	VERSION	TKPH	O.W. (MM)	O.D. (MM)	SLR (MM)	RC (MM)	TREAD DEPTH (MM)	RIM	
													REC.	ALT.
	33.00 R 51	E4	**	235 B	TL	CRC	558	905	3050	1401	9377	87.0	24.00/5.0	-
	33.00 R 51	E4	**	235 B	TL	STD	697	905	3050	1401	9377	87.0	24.00/5.0	-

CRC: CUT RESISTANT COMPOUND - HRC: HEAT RESISTANT COMPOUND - STD: STANDARD COMPOUND

Bar	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
km/h	Load capacity (kg/tire)								
50	30000	30750	32500	33500	34500	35500	36500	37500	38750



BKT
GROWING TOGETHER