

SPINJET®

FLOOR AND GRATE CLEANERS

REDUCE
**LABOR,
OPERATING
COSTS** AND
ENERGY USE.



Our SpinJet® floor and grate cleaners (maneuvered like a lawn mower) were originally designed to remove overspray from paint booth grates. Today they are also widely used for removing floor and ship deck coatings, highway stripes, runway rubber, and more... and even for concrete scarification. Standard features include a dump valve that instantly reduces water pressure to near-zero and shields over moving components, hose and quick-disconnects. Rotary seal and dump valve repair kits are available. Options include 4-arm and 6-arm configurations and pneumatic or hard rubber tires. Some models have vacuum recovery.

SPINJET™



**ALL UNITS ARE CERTIFIED AND
FACTORY TESTED BEFORE SHIPMENT**
Specifications subject to change without notice.

HOW TO CHOOSE A SPINJET®

NLB recommends self-rotating seals for most applications, as they allow faster rotating speeds without any power connection. However, pneumatically or hydraulically powered seals are excellent for controlling speed when flow rates are low. Here's a quick comparison:

Self-Rotating

- Faster rotation speeds
- No need for compressed air
- Only one hose hook-up
- Economical to operate and maintain

Air-Powered

- Consistent speed at low flows
- Ideal with lower horsepower pumps
- Pneumatic



LEADING WATER JET TECHNOLOGY™
NLBCORP.COM

© Copyright 2018 NLB Corp.

SPINJET® FLOOR AND GRATE CLEANERS

ACCESSORIES



36-9950-15A**



36-9900-15A*



24-9900-15A
10-9900-15A



1115-20K



1115



1550-20K
1550

RECOMMENDED SPARE PARTS KIT: *36-9990-15A-1 ** 36-9950-15A-1

| MODEL | 36-9950-15A** | 36-9900-15A* | 24-9900-15A | 1550-20K | 1115-20K | 10-9900-15A | 1550 | 1115 |
|---------------------------|--------------------------------------|--------------------------------------|-------------------------|------------------------|------------------------|-------------------------|----------------------|-------------------------------|
| TYPE | Air-Powered | Air-Powered | Air-Powered | Self-Rotating | Self-Rotating | Air-Powered | Self-Rotating | Self-Rotating |
| SEAL MODEL | DRS12481 | DRS12481 | DM24431 | NLB3620 | NLB3620-2 | DM17135 | NLB1535 | NLB1535 |
| DISCHARGE PRESSURE (MAX.) | 40,000 psi (2,760 bar) | 40,000 psi (2,760 bar) | 24,000 psi (1,656 bar) | 20,000 psi (1,380 bar) | 20,000 psi (1,380 bar) | 10,000 psi (690 bar) | 10,000 psi (690 bar) | 10,000 psi (690 bar) |
| MAX. FLOW | 11 gpm (42 lpm) | 11 gpm (42 lpm) | 20 gpm (76 lpm) | 50 gpm (189 lpm) | 25 gpm (95 lpm) | 32 gpm (121 lpm) | 50 gpm (189 lpm) | 50 gpm (189 lpm) |
| ROTATION SPEED | 2,000 rpm | 2,000 rpm | 2,000 rpm | 3,000 rpm | 3,000 rpm | 2,000 rpm | 3,000 rpm | 3,000 rpm |
| AIR | 65 psi @ 50 cfm (4.5 bar @ 23.6 l/s) | 65 psi @ 50 cfm (4.5 bar @ 23.6 l/s) | N/A | N/A | N/A | N/A | N/A | N/A |
| WEIGHT | 162 lbs (73.5 kg) | 134 lbs (60.8 kg) | 180-235 lbs (82-107 kg) | 250 lbs (113 kg) | 270 lbs (122 kg) | 160-295 lbs (73-134 kg) | 250 lbs (113 kg) | 267 lbs (121 kg) |
| AVAILABLE WIDTHS | 16" (41 cm) | 16" (41 cm) | 13" (33 cm) | 20" (51 cm) | 18", 24" (46, 61 cm) | 13" (33 cm) | 20" (51 cm) | 18", 24", 30" (46, 61, 76 cm) |
| DUMP VALVE MODEL | DSJ12260 | DSJ12260 | DM24495 | V20-550-00 | CV8274 | DM16940 | V-550 | V-550 |
| NOZZLES | Up to 15 | Up to 15 | N/A | N/A | N/A | N/A | N/A | N/A |



HEADQUARTERS
Wixom, MI
(248) 624-5555

REGIONAL OFFICES
Located across the
United States and Europe

LEADING WATER JET TECHNOLOGY™
NLBCORP.COM

© Copyright 2018 NLB Corp.

P-SST_20180411-SpinJetSellSheet_v4