



Technical Specifications

Black Beauty

Frame weight: 20.4 lbs.

w/ engine (dry): 31 lbs.

Length: 51.25 in.

Width @ lower: 19.5 in.

Width @ top (T-handle): 26.5 in.

Upper drive system: flex shaft w/ coupling

Lower drive system: heavy duty solid short shaft
w/ sealed bearings

Recommended bar lengths:
4' - 20' Equilateral triangle bars

Electric Beauty

Frame weight: 11.5 lbs.

w/ motor: 22 lbs.

Length: 53.5 in.

Width @ lower: 18 in.

Width @ top (T-handle): 26.5 in.

Upper drive system: flex shaft

Lower drive system: Heavy duty solid short shaft
w/ tapered roller bearings

Recommended bar lengths:
4' - 12' Equilateral triangle bars

Silver Beauty

Frame weight: 11.5 lbs

w/ engine (dry) 21 lbs

Length: 53.5 in. (Including t handle)

Width @ lower: 18 in.

Width @ top (T-handle): 26.5 in.

Upper drive system: flex shaft

Lower drive system: Heavy duty solid short shaft
w/ tapered roller bearings

Recommended bar lengths:
4' - 14' Equilateral triangle bars

Screed Bars

Equilateral triangle bar design creates horizontal as well as vertical vibration patterns, simultaneously enabling compaction and a bump cutting effect

Reinforced design prevents twisting, warping or bending, ensuring the best possible F numbers

Sizes available: 4, 6, 8, 10, 12, 14, 16 and 20 ft. Additionally, custom sizes are available for order

Engine (Honda GX35)

Engine Type: Air-cooled 4-stroke OHC

Bore x Stroke: 39 mm x 30 mm

Displacement: 35.8 cm³

Net power output: 1.3 HP (1.0 kW) @ 7,000 rpm

Net torque: 1.2 lb-ft (1.6 Nm) @ 5,500 rpm

Dry weight: 7.6 lb (3.3 kg)